


## Ergomat Classic Mat

The Classic Mat is the original ergonomic bubble profile mat. The Classic Mat boasts the longest warranty in the industry. Customers still have many of these original mats in service over 20 years later. Available in 2 profiles: **Classic** and **Classic Deluxe**.

CLASSIC DELUXE

CLASSIC



2 Profiles

Classic Deluxe

Classic



Thickness .6" (1.5 cm)



Thickness .6" (1.5 cm)

## BENEFITS

**ERGONOMIC** : Designed to stimulate circulation in feet, legs and lower back. Circulation is stimulated by the unique, patented surface profile of Ergomat mats, which forces muscular response.

**BEVELED EDGES** : Molded w/ bevels. Yellow bevels can be added. Bevels will never curl up, eliminating trip hazards.

**ANTI-STATIC** : Ideal for environments requiring static control.

**ISO CLEANROOM CERTIFIED** : Classic Mats are ISO Cleanroom Class 5 (Class 100) rated .

**ANY SIZE ANY SHAPE**: Can be custom made in any size and shape, creating one continuous surface to eliminate seams and trip hazards.

**SILICON FREE**: All Ergomat mats are silicon free.

**TRUE WARRANTY**: Ergomat stands 100% behind our products with full replacement coverage if our product fails to perform as promoted within that period. At Ergomat we call this a *True Warranty*.

[www.ergomat.se](http://www.ergomat.se) - [info@ergomat.se](mailto:info@ergomat.se)

North & South America: +1-440-282-4651 | English (EU): +44 3308 280 084 | Danish: +45 702 21 840 | Dutch: +31 73 61 30 530 | Swedish: +46 42 16 36 00  
German: +49 9542 30 367-50 | French: +33 1 446 410 28

Rev. 11/27/2018

# Ergomat Classic Basic

	CLASSIC	CLASSIC DELUXE
Material.....	Foamed Polyurethane	
Color .....	Grey	
Weight.....	2500 g +/- 50 g // 5.5 lbs +/- 0.1 lbs	2790 g +/- 50 g // 6.15 lbs +/- 0.1 lbs
Length without beveled edges ..	91 cm +/- 1% // 35.8" +/- 0.38"	
Width without beveled edges...	60 cm +/- 1% // 23.6" +/- 0.38"	
Thickness .....	15 mm // 0.6"	15 mm // 0.6"
Density.....	380 kg/m <sup>3</sup> +/- 10 % ISO 2781	
Hardness .....	22-30 Sh A DIN 53505	
Compression Pressure face = ø 100mm % by pressure of 240kg .....	50% Tinby A/S Standard	
Abrasion Load = 5 N .....	180 mm <sup>3</sup> // 7 in <sup>3</sup> ISO 46 49 (5 N)	
Electrical Resistance Surface point to point % 50 RH .....	1x10 <sup>9</sup> Ω-5x10 <sup>9</sup> Ω ESDSTM7	
Breaking Point/Tensile Strength	2 Mpa EN ISO 527-1	
Elongation at Break	500% EN ISO 527-1	
Tearing Strength .....	4 N/mm ASTM D 624	
Thermal properties		
Minimum use.....	0°C // 32°F	
Maximum use .....	32°C // 90°F	
Maximum short duration	40°C // 115°F	
UV-Resistance .....	Inferior	
Hydrolic Resistance .....	Inferior	
Cleanroom Application.....	ISO Class 5 (100) EN ISO 14644-1	
Warranty.....	8 years	

[www.ergomat.se](http://www.ergomat.se) - [info@ergomat.se](mailto:info@ergomat.se)

North & South America: +1-440-282-4651 | English (EU): +44 3308 280 084 | Danish: +45 702 21 840 | Dutch: +31 73 61 30 530 | Swedish: +46 42 16 36 00  
 German: +49 9542 30 367-50 | French: +33 1 446 410 28